

PLASTERMIX PRO

Single component water resistance monolith plastering/rendering ready-mix mortar

ABOUT THE PRODUCT

Admyx PlasterMix PRO is a singular, all-inclusive monolithic plastering and rendering mortar with remarkable water resistance. Its precise blend includes graded inert sand, cement, and advanced polymers, showcasing cutting-edge construction innovation and designed for diverse civil engineering projects. It is suitable for internal and external applications providing the following key features:

- Cohesive workable mortar facilitating efficient application.
- This mortar is engineered to improve tensile and flexural strength.
- Reduced wall porosity and voids thus enhancing the overall structural integrity.
- Elimination of cement slurry application for plastered surface.
- The mortar results in a uniform and smooth finishes.
- Enhanced bond strength with applied substrate.
- The incorporation of polymers and specialized components in the mortar formulation enhances its durability.

SURFACE PREPARATION

- Clean surface, free from grease and particles, is essential.
- Porous, absorbent substrates need SSD (Saturated Surface Dry) condition.
- Pre-wet substrate to prevent early water loss from plaster.

APPLICATION

Apply the plaster onto the substrate, exerting pressure, and finalize the process using a trowel or float. This guarantees the optimal bonding of the plaster to the substrate surface.

PRODUCT PROPERTIES

- Appearance : Grey powder
- Bulk Density : 1.45-1.50 gm/cc
- Water Demand Ratio : 0.15-0.16
- Finish : Smooth, uniform, void free

COVERAGE

For walls: Mix Admyx PlasterMix PRO, one component, with water/powder ratio of 0.15-0.16. Achieve 5-15 mm thickness, covering 0.175 to 0.20 Kg/sq.ft./mm for a flawless surface finish.

For ceilings: Mix Admyx PlasterMix PRO, a single component, with water/powder ratio of 0.15-0.16. Achieve 5-12 mm thickness, covering 0.175 to 0.20 Kg/sq.ft./mm for a consistent and desired contour.

PACKING

40 KG BOPP Bags

SHELF LIFE

Under normal ambient temperatures and when stored in unopened containers, Admyx PlasterMix PRO has a shelf life of approximately 6 months.

MATERIAL SAFETY DATA

Admyx PlasterMix PRO is a non-toxic and non-flammable material. While handling, it is advisable to avoid skin contact as much as possible. The product should be stored in a shaded area away from direct sunlight.

Corporate Office

Room No. 8, 1st Floor, 23A Netaji Subhas Road, Kolkata, Pin. - 700001

Factory Office

Vill. - Jagadispur (Bakultala), P.O. - Bamangachi P.S. - Baruipur, Dist. - 24 PGNS (S), Pin. - 700145