

ADMYX MOLDRELEASE PRO WT

Emulsified Mineral Oil Based Water thin able Shutter
Release Agent

ABOUT THE PRODUCT

Admyx Moldrelease Pro WT is a combination of refined emulsified mineral oil, when distilled with water it produces a chemical release agent. It has the economy of a conventional oil with outstanding properties of a stable release agent.

USES

To provide quick, clean and easy stripping of moulds or framework. To obtain clean and smooth concrete surface. To protect steel and wooden framework

APPLICATION

Apply one coat only by brush, roller or spray on the cleaned surface. Admyx Moldrelease Pro WT after application should be allowed to dry before concreting takes place.

ADVANTAGES

- Requires only water for use
- Minimum cleaning of shutters before re use
- Extended life of form work
- Can be used on all types of formwork
- Improved finish: stain free fair faced concrete
- Non Corrosive to steel
- Dust free concrete surfaces

PRODUCT PROPERTIES

- Appearance : Light brownish liquid
- Specific Gravity : 0.84 to 0.86 at 27° C
- Coverage : 30-40 M² / litre, wood & 40-50 M² / litre, steel or plastic, consumption depends upon the surface texture and porosity of the frame work.

Coverage after dilution, dilution rate (Moldrelease Pro Wt: Water = 1:6)

PACKING

20, & 250 Lts BOPP Drums.

SHELF LIFE

Can be stored for approx. 12 months in tightly closed packs in dry and cool place.

MATERIAL SAFETY DATA

Admyx Moldrelease Pro WT container should be protected from sunlight and naked flame. It is non toxic, and ingestion is to be avoided. Any splashes to the skin must be washed with water. If contact with eyes occurs, wash well immediately with water and seek medical advice.

Corporate Office

Room No. 8, 1st Floor, 23A Netaji Subhas Road,
Kolkata, Pin. - 700001

Factory Office

Vill. - Jagadispur (Bakultala), P.O. - Bamangachi,
P.S. - Baruipur, Dist. - 24 PGNS (S), Pin. - 700145